

# **PARTNER**

CARE . TRUST . RESPONSIBILITY

## All-in-One Touch Terminal PT-6215

### Be flexible and independent



The PT-6215 All-in-One POS Touch Terminal is the perfect solution for all kind of businesses.

The compact and elegant design fits into every environment installation and is extremely counter space saving.

As the PT-6215 is an All-in-One Terminal, it can be easy installed without extra modules, cables etc.

It is the perfect POS Terminal for everyone who wants to be independent and flexible.

#### **Special Features:**

- Elegant, compact and fanless design
- 15" TFT-LCD touch screen
- Open architecture
- Modular design for easy maintenance
- Integrated 3-track MSR
- 80 mm Epson thermal printer
- 2x20 VFD customer display

#### **Optional:**

- Solid State Drive
- RAID
- RFID module
- WiFi module

## All-in-one POS Terminal PT-6215

### Technical data

Item	PT-6215									
CPU	Intel Atom N270 @ 1.6GHz/512K L2 cache									
Chipset	Intel 945GSE + ICH7M									
Memory	System chips with DDR2 1GB std, support up to 2GB									
LCD	15" TFT-LCD									
Resolution	1024 x 768									
Touch	5-wire resistive touch									
LCD Brightness	250 cd/m <sup>2</sup> (w/o touch)									
LAN	10/100/1000Mbps on board Ethernet controller									
Storage	IDE 3.5" HDD or optional SATA SSD									
I/O ports	4 x COM ports 1 x RJ11 port (+24V) 1 x PS/2 Keyboard port 1 x RJ-45 LAN port 5 x USB ports 1 x DC +12V 1 x VGA port									
Operation System	WEPOS / POSReady / Windows XP Pro / Windows XP embedded / Windows 7 / Linux									
Power Supply	AC 100V~240V / DC12V / 15A 180 watt power adaptor									
Environment	<table border="1"> <thead> <tr> <th></th> <th>Operating</th> <th>Storage</th> </tr> </thead> <tbody> <tr> <td>Temperature</td> <td>0~40 °C</td> <td>C -20~60 °C</td> </tr> <tr> <td>Humidity</td> <td>15% ~ 80%</td> <td>15% ~ 80%</td> </tr> </tbody> </table>		Operating	Storage	Temperature	0~40 °C	C -20~60 °C	Humidity	15% ~ 80%	15% ~ 80%
	Operating	Storage								
Temperature	0~40 °C	C -20~60 °C								
Humidity	15% ~ 80%	15% ~ 80%								
Dimension	345 mm (W) x 321 mm (D) x 256 mm (H)									
Integrated Peripherals	3-Track MSR, 2 x 20 VFD customer display, 80 mm Thermal Epson printer with auto cutter									
Options	Solid State Drive, RAID, RFID module, WiFi module									



15" TFT-LCD Touch Screen



3-Track MSR



80mm Epson Thermal printer with Auto Cut and Paper Feed



Rear VFD Customer Display



Compact and small footprint



Modular design for easy maintenance

