

# PARTNER

CARE . TRUST . RESPONSIBILITY

## Service Caller System

### Enhance your service



The Service Caller System is an intelligent product for the F&B service enhancement.

The customer presses the Caller when he is in need of service and his table number will be shown on the digital display in the service area.

With high sensitivity wireless connection up to 150 meters transmits range, anytime and anywhere, the Service Caller System helps to offer quick service and a better customer satisfaction.

#### Special Features

**High-sensitivity wireless connection up to 150m transmits range**

**Up to 998 service call systems in single area**

**16 types of service tone selections with adjustable volume**

**Low battery LED indicator**

## Service Caller System



### Technical Datas

SCR	Service caller Receiver
Frequency	433MHz/ 868MHz / 902MHz
Sensitivity	-105dBm@ 12dB SINAD
Modulation	FSK
Remote Distance	Max. 150M (Open environment)
Display type	4inch 7 stage displayer x 3
Power supply	DC 12V/1A stable voltage power supply
Power Consumption	Stand by: 28mA; Active: Max. 700mA
Environment	Operation Temperature: -10° C~ 40°C Storage Temperature: -20°~60°C Storage Humidity: 10%~90%
Dimensions	370 mm(L) x 205 mm(W) x 45 mm(H)
Others	Status LED indicator X 4

  

SCT	Service caller Transmitter
Frequency	433MHz/ 868MHz / 902MHz
RF Power	10mW
Modulation	FSK
Power supply	Alkaline Batter (AAA)X2
Power Consumption	Standby:20uA;Active:37mA
Environment	Operation Temperature: -10° C~ 55°C Storage Temperature: -20°~60°C Storage Humidity: 10%~90%
Dimensions	68 mm(D) x 28.5 mm(H)
Others	Status LED indicator X 1 (Green), Low Battery LED X 1(Red)

